

Practitioner's D k t N . 60680-727

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of: Werson et al. Group No.: Unassigned
Application No.: 10 / 671,380
Filed: 09-25-03 Examiner: Unassigned
For: AN ELECTRIC MOTOR

Assistant Commissioner for Patents
Washington, D.C. 20231

TRANSMITTAL OF CERTIFIED COPY

Attached please find the certified copy of the foreign application from which priority is claimed for this case:

Country: United Kingdom

Application
Number: 0222440.0

Filing Date: 09-27-2002

WARNING: "When a document that is required by statute to be certified must be filed, a copy, including a photocopy or facsimile transmission of the certification is not acceptable." 37 C.F.R. § 1.4(f) (emphasis added).

SIGNATURE OF PRACTITIONER

Reg. No. 41,908

William F. Kolakowski III

(type or print name of practitioner)

Tel. No. (248) 203-0822

Dykema Gossett PLLC
39577 Woodward Avenue, Suite 300

P.O. Address

Customer No.: 26127

Bloomfield Hills, MI 48304-2820

NOTE: The claim to priority need be in no special form and may be made by the attorney or agent, if the foreign application is referred to in the oath or declaration, as required by § 1.63.

CERTIFICATE OF MAILING (37 C.F.R. § 1.8a)

I hereby certify that this correspondence is, on the date shown below is being deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Date: 12/16/03

Signature

Linda K. Garayola
(type or print name of person certifying)

(Transmittal of Certified Copy [5-4])



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.


In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated 30 September 2003

Patents Form 1/77

Patents Act 1977
(Rule 16)

1/77

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

 Cardiff Road
 Newport
 South Wales
 NP10 8QQ
1. Your reference

A10612GB - DJL/ACL/h 27SEP02 F751493-1 D02811

00-0222440.0

2. Patent application number

(The Patent Office will fill in this part)

0222440.0

3. Full name, address and postcode of the or of each applicant (underline all surnames)
 Automotive Motion Technology Limited
 Fellows House, Royce Close
 West Portway Industrial Estate
 Andover, Hampshire
 ST10 3TS

Patents ADP number (if you know it)

7372147001

 If the applicant is a corporate body, give the
 country/state of its incorporation

United Kingdom

4. Title of the invention An Electric Motor**5. Name of your agent (if you have one)**

Forrester Ketley & Co.

 "Address for service" in the United Kingdom
 to which all correspondence should be sent
 (including the postcode)

 Chamberlain House
 Paradise Place
 Birmingham
 B3 3HP

Patents ADP number (if you know it)

133005

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

 Priority application number
 (if you know it)

 Date of filing
 (day / month / year)
7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

 Date of filing
 (day / month / year)
8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes if'

a) any applicant named in part 3 is not an inventor, or

b) there is an inventor who is not named as an applicant, or

c) any named applicant is a corporate body.

See note (ii)

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form	-
Description	6
Claim(s)	2
Abstract	1
Drawing(s)	2 only

CF

10. If you are also filing any of the following, state how many against each item.

Priority documents	-
Translations of priority documents	-
Statement of inventorship and right to grant of a patent (Patents Form 7/77)	-
Request for preliminary examination and search (Patents Form 9/77)	One
Request for substantive examination (Patents Form 10/77)	-
Any other documents (please specify)	-

11. I/We request the grant of a patent on the basis of this application.

Forrester Ketley & Co. Signature

Date
27 September 2002

12. Name and daytime telephone number of person to contact in the United Kingdom
- David Lucking
0121 236 0484

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered "Yes" Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

DUPLICATE

PATENTS ACT 1977

A10612GB-DJL/ACL

Title: An Electric Motor

Description of Invention

The present invention relates to an electric motor.

In an electric motor where a rotor is mounted outside a stator for rotation around the stator, the rotor typically includes a generally cylindrical rotor wall, and a plurality of permanent magnets or other magnetic field producing elements mounted on an inside surface of the rotor wall. The cylinder of the rotor wall is closed at one end by a top which provides a mounting for a central rotor shaft, the motor shaft being mounted for rotation within the stator, about its longitudinal axis.

It is known to mount the rotor top on the motor shaft by means of a bush formed from the rotor top, the shaft engaging with the bush as an interference fit. In order to provide such a connection, however, the rotor top must be sufficiently thick to provide enough material to form such a bush. As the rotor top and rotor wall are typically formed from a single sheet of metal, the sheet needs to be of a thickness such that there is sufficient material to form the bush on the rotor top. Such a thick sheet metal provides a substantial contribution to the weight of the rotor, and is overly thick in comparison to the minimum thickness needed for the rotor wall to provide support for the magnets.

It is also known to weld the shaft onto the rotor top, but this is time-consuming and is inconvenient.

According to a first aspect of the invention we provide an electric motor including a rotor mounted on a motor shaft for rotation around a stator, the rotor including a generally cylindrical wall and a rotor top generally closing the cylinder of the rotor wall, the rotor being connected to the motor shaft by a connecting device, the connecting device being received within an opening in the rotor top and having an aperture for receiving the motor shaft as an

interference fit which prevents of rotation of the shaft with respect to the connecting device, the connecting device including a first radially outwardly extending formation at a first side of the rotor top, and a second radially outwardly extending formation at a second side of the rotor top such that the rotor top is received between the first and second radially outwardly extending formations, and there being a spacer between the first radially outwardly extending formation and the first side of the rotor top, the spacer including teeth which dig into the first side of the rotor top and the first radially outwardly extending formation to prevent of rotation of the connecting device with respect to the rotor.

Thus, by virtue of the invention, a rotor top is connected to a motor shaft without the need for welding or forming a bush from the rotor top.

The motor shaft and walls of the aperture in the connecting device are preferably splined in order to provide an enhanced interference fit.

The connecting device may include a generally cylindrical body portion through which the aperture is provided, which body portion extends through the opening provided in the rotor top. In this case, the first radially outwardly extending formation may extend from a first end of the body portion, and the second outwardly extending formation may extend from a second end of the body portion.

The spacer is preferably an annular member such as a washer, which is located around the body portion of the connecting device

According to a second aspect of the invention we provide a method of assembling an electric motor, the electric motor including a rotor having a generally cylindrical rotor wall and a rotor top generally closing the cylinder of the rotor wall, the rotor being mounted on a motor shaft for rotation about a stator, the motor further including a connecting device adapted for connecting the rotor top to the motor shaft, the method including the step of mechanically deforming a portion of the connecting device so as to form a first radially

3

outwardly extending formation, such that the rotor top is clamped between the first radially outwardly extending formation and a second radially outwardly extending formation of the connecting device and movement of the rotor with respect to the connecting device is substantially prevented.

Thus, by virtue of the invention, the need for forming a bush from the rotor or for welding a bush onto the rotor is avoided.

Preferably, the method further includes the step of inserting the motor shaft into an aperture provided in the connecting device such that the shaft engages with the connection device as an interference fit and rotational movement of the motor shaft with respect to the connecting device is substantially prevented.

The invention will now be described with reference to the accompanying drawings, of which,

FIGURE 1 is an illustration of an electric motor according to the first aspect of the invention,

FIGURE 2 is an illustration of a longitudinal section through part of the electric motor of Figure 1, and

FIGURE 3 is an illustration of the spacer of Figure 2.

Referring now to Figure 1, there is shown an electric motor including a rotor 10 and a stator 11, the rotor 10 being adapted in use to rotate around the stator 11. The rotor 10 includes a generally cylindrical rotor wall 12a, and a rotor top 12b which closes the cylinder of the rotor wall 12a. A plurality of magnetic field producing elements, in this case permanent magnets 14, are mounted around an inside surface of the rotor wall 12a.

The rotor 10 is mounted on a motor shaft 18 which extends through a generally central circular opening provided in the rotor top 12b axially of the rotor wall 12a. The shaft 18 is mounted for rotation about its longitudinal axis A.

The shaft 18 is connected to the rotor top 12b by means of a connecting device 20, which includes a generally cylindrical body portion 18a and has an aperture extending axially through the body portion 18a. A portion of the motor shaft 18 extends through the aperture in the body portion 18a, and is retained therein as an interference fit. To improve the interference fit and to reduce the possibility of the shaft 18 rotating in the aperture, both the shaft 18 and inside walls of the aperture are splined.

The connecting device 20 further includes a first and a second radially outwardly extending formation 21b, 21c, which extend radially outwardly from a first and second end of the body portion 18a respectively. The body portion 21a is received in the opening provided in the rotor top 12b, and the first radially outwardly extending formation 21b is adjacent to a first side of the rotor top 12a, and the second radially outwardly extending formation 21c is adjacent to the second side of the rotor top 12a.

A spacer 22, in this example an annular member such as a washer 22, is arranged around the body portion 21a of the connecting device 20 between the first side of the rotor top 12a and the first outwardly extending formation 21b. The first outwardly extending formation 21b bears on the washer 22 to clamp the rotor top 12b between the washer 22 and the second outwardly extending formation 21c, substantially to prevent movement of the connecting device 20 with respect to the rotor 10.

In order to minimise the possibility that the connecting device 20 may be able to rotate with respect to the rotor top 12, the washer 22 is provided with a plurality of teeth 22a on its upper and lower surfaces, as shown in Figures 2 and 3. In this example, the teeth 22a are ridges which extend radially of the washer 22, but the teeth 22a may instead include radial rows of discrete spikes, for example.

It should be noted that the size of the teeth 22a relative to the remainder of the motor has been significantly exaggerated for clarity. The teeth 22a may, for example, be only of the order of a few microns high.

Teeth 22a on the upper surface of the washer 22 dig into the first radially outwardly extending formation 21b of the connecting device 20, and teeth 22a on the lower surface of the washer 22 dig into the first side of the rotor top 12b. Thus the teeth 22a enhance mechanical locking between the washer 22 and the rotor top 12a and the connecting device 22.

By virtue of the radial arrangement of the teeth 22a, the teeth 22a may prevent, or at least substantially prevent the washer 22 from rotating about axis A with respect to the rotor 10 or the connecting device 20.

The rotor 10 is connected to the shaft 18 as follows.

The connecting device 20 is supplied with the material which will make up the first radially outwardly extending formation 21b forming a continuation of the cylindrical body portion 21a. The cylindrical body portion 21a is inserted through the opening in the rotor top 12b such that the second radially outwardly formation 21c is enclosed by the rotor wall 12a and engages with the second side of the rotor top 12b. The washer 22 is then inserted over the first lip 21b and placed around the body portion 21a of the connecting device 20.

The shaft 18 is inserted into the shaft retaining portion 21a either before the connecting device 20 is fitted through the aperture in the rotor top 12b, or before or after the washer 22 is placed around the body portion 21a.

The connecting device 20 is then mechanically deformed to form the first radially outwardly extending formation 21b and to ensure that the first radially outwardly extending formation 21b engages with an upper surface of the washer 22 and clamp the rotor top 21b between the washer 22 and the second radially outwardly extending formation 21c. This may be achieved by peening or some other form of forging.

As the first radially outwardly extending formation 21b engages with the upper surface of the washer 22, at least some of the teeth 22a provided on the upper surface of the washer 22 dig into the first radially outwardly extending formation 21b. Similarly, as the washer 22 is forced down onto the first side of the rotor top 12b, at least some of the teeth 22a provided on the lower surface of the washer 22 dig into the first side of the rotor top 12b. Thus, movement of the shaft 18 with respect to the rotor 10 is substantially prevented, without the need for welding or forming a bush from a thick-walled rotor top 12b.

In order to reduce the noise generated by the motor it is possible to make the rotor wall 12a and/or top 12b from a layered material comprising two sheets of metal or other rigid material separated by a layer of visco-elastic material. An example of such a material is sold commercially under the trade mark BONDAL®.

Alternatively, or additionally, it is possible to make the washer 22 from such a layered material, and this has been found to assist in damping vibration of the rotor 12, particularly when the motor is operating at high speed.

The features disclosed in the foregoing description, or the following claims, or the accompanying drawings, expressed in their specific forms or in terms of a means for performing the disclosed function, or a method or process for attaining the disclosed result, as appropriate, may, separately, or in any combination of such features, be utilised for realising the invention in diverse forms thereof.

CLAIMS

1. An electric motor including a rotor mounted on a motor shaft for rotation around a stator, the rotor including a generally cylindrical wall and a rotor top generally closing the cylinder of the rotor wall, the rotor being connected to the motor shaft by a connecting device, the connecting device being received within an opening in the rotor top and having an aperture for receiving the motor shaft as an interference fit which prevents of rotation of the shaft with respect to the connecting device, the connecting device including a first radially outwardly extending formation at a first side of the rotor top, and a second radially outwardly extending formation at a second side of the rotor top such that the rotor top is received between the first and second radially outwardly extending formations, and there being a spacer between the first radially outwardly extending formation and the first side of the rotor top, the spacer including teeth which dig into the first side of the rotor top and the first radially outwardly extending formation to prevent of rotation of the connecting device with respect to the rotor.
2. A motor according to claim 1 wherein the motor shaft and walls of the aperture in the connecting device are splined.
3. A motor according to claim 1 or 2 wherein the connecting device includes a generally cylindrical body portion through which the aperture is provided, which extends through the opening provided in the rotor top.
4. A motor according to claim 3 wherein the first radially outwardly extending formation extends from a first end of the body portion, and the second outwardly extending formation extends from a second end of the body portion.

5. A motor according to claim 3 or 4 wherein the spacer is an annular member, which is located around the body portion of the connecting device.

6. A motor substantially as hereinbefore described with reference to and/or as shown in the accompanying drawings.

7. A method of assembling an electric motor, the electric motor including a rotor having a generally cylindrical rotor wall and a rotor top generally closing the cylinder of the rotor wall, the rotor being mounted on a motor shaft for rotation about a stator, the motor further including a connecting device adapted for connecting the rotor top to the motor shaft, the method including the step of mechanically deforming a portion of the connecting device so as to form a first radially outwardly extending formation, such that the rotor top is clamped between the first radially outwardly extending formation and a second radially outwardly extending formation of the connecting device and movement of the rotor with respect to the connecting device is substantially prevented.

8. A method according to claim 7 wherein the method further includes the step of inserting the motor shaft into an aperture provided in the connecting device such that the shaft engages with the connection device as an interference fit and rotational movement of the motor shaft with respect to the connecting device is substantially prevented.


9. A method of assembling an electric motor substantially as hereinbefore described with reference to the accompanying drawings.

10. Any novel feature or novel combination of features hereinbefore described and/or shown in the accompanying drawings.

ABSTRACT

Title: Electric Motor

An electric motor including a rotor (10) mounted on a motor shaft (18) for rotation around a stator (11), the rotor (10) including a generally cylindrical wall (12a) and a rotor top (12b) generally closing the cylinder of the rotor wall (12a), the rotor (10) being connected to the motor shaft (18) by a connecting device (20), the connecting device (20) being received within an opening in the rotor top (12b) and having an aperture for receiving the motor shaft (18) as an interference fit which prevents of rotation of the shaft (18) with respect to the connecting device (20), the connecting device (20) including a first radially outwardly extending formation (21b) at a first side of the rotor top (12b), and a second radially outwardly extending formation (21c) at a second side of the rotor top (12b) such that the rotor top (12b) is received between the first and second radially outwardly extending formations (12b, 12c), and there being a spacer (22) between the first radially outwardly extending formation (12b) and the first side of the rotor top (12b), the spacer (22) including teeth (22a) which dig into the first side of the rotor top (12b) and the first radially outwardly extending formation (21b) to prevent of rotation of the connecting device (20) with respect to the rotor (10).



2 / 2

